

balanced


MY250

Microphone Cable - 2 x 0.50 mm²


- 0.50 mm² conductor cross section
- PE inner jacket for stabilising pair twisting




Microphone

 Conductor	stranded bare copper, 16 x 0.20 mm
Cross Section	0.50 mm ²
Insulation	PE
Core Arrangement	2 cores twisted to a pair
Inner Jacket	extruded inner covering from PE
Shielding	bare copper braid
Jacket	PVC
Overall Diameter	5.6 mm

Leiteraufbau	blanke Cu-Litze, 16 x 0,20 mm
Leiterquerschnitt	0,50 mm ²
Isolation	PE
Aderanordnung	2 Adern zum Paar verseilt
Innenmantel	gemeinsame Aderumhüllung aus PE
Abschirmung	blankes Cu-Geflecht
Außenmantel	PVC
Außendurchmesser	5,6 mm

 Min. Bending Radius	40 mm
Working Temperature	-20 °C / +70 °C

Min. Biegeradius	40 mm
Betriebstemperatur	-20 °C / +70 °C

 Conductor Resistance	< 40 Ω/km
Capacitance	60 pF/m
Insulation Resistance	> 10 GΩ x km

Leiterwiderstand	< 40 Ω/km
Betriebskapazität	60 pF/m
Isolationswiderstand	> 10 GΩ x km

■ SW [black]

Order Code Bestell-Nr.	Colour Farbe	Weight Gewicht	Standard Length [m] Standard Längen [m]	Max. Length / Reel Max. Länge / Spule
MY250CY	black	45 g/m	100 / 500	2000 m